

Discover how you can have your disconnection boxes installed in five minutes flat and save money in the process!

- No need for CAT scanning, so it avoids cable strikes!
- There's no more need for digging holes.
- Can be installed by a single operative.
- No more carrying water and bags of Drymix.
- Disconnection boxes at the same height relative to the cable route every time.



The installation process is simple...

...step 1: Remove the lid from the cable route...



...step 2: Knock out the cable entry point on the cable route...



...step 3: Place the bracket on the route...



...step 4: Replace the trough lid...



...step 5: Terminate the cable in the disconnection box.



Also available, brackets for Tuning Units, HVI and Points disconnection boxes



Please contact us for further details!

UK Patent application number GB 0505061.2

GM Rail Services Ltd, 65 Somers Road, Rugby, CV22 7DG

DISCONNECTION BOX BRACKET Product and Application Range

PRODUCT CODE:GM/DiBB/B Disconnection Box Bracket

AWS Disconnection Boxes / Track Circuit Disconnection Boxes / 4 by 4 Points Disconnection Box



PRODUCT CODE:GM/DiBB/D Disconnection Box Bracket for Tuning Units



PRODUCT CODE:GM/DiBB/F Disconnection Box Bracket for HVI Box



PRODUCT CODE:GM/DiBB/H Disconnection Box Bracket for Points Disconnection Box 10 by 4

